

Pilot Vehicle and TCP Requirements

OR126 Ochoco Highway HWY 041 (MP 0.22 – MP 18.16) Redmond to Prineville

Width:	Requirements:
UP TO 16'	ONE FRONT AND ONE REAR PILOT CARS MINIMUM
16'1' – 17'	THREE FRONT AND ONE REAR PILOT CARS MINIMUM
17'1" – 18'	THREE FRONT AND ONE REAR PILOT CARS MINIMUM EXCEPT: MP 1.30 – MP 1.63 FULL CLOSURE
18'1" – 19'	THREE FRONT AND ONE REAR PILOT CARS MINIMUM EXCEPT: MP 1.30 – MP 1.63 MP 11.00 – MP 13.52 FULL CLOSURE
19'1" – 20'	THREE FRONT AND ONE REAR PILOT CARS MINIMUM EXCEPT: MP 1.30 – MP 1.63 MP 11.00 – MP 13.52 FULL CLOSURE
20'1" – 21'	THREE FRONT AND ONE REAR PILOT CARS MINIMUM EXCEPT: MP 0.49 – MP 16.51 FULL CLOSURE
21'1" and OVER	CASE BY CASE PER DISTRICT APPROVAL (THREE FRONT AND ONE REAR MINIMUM)

Additional Limitations & Exceptions:

Over-Dimension Permit analysts allowed to permit travel on OR126 from MP 0.22 to MP 18.16, up to 17' wide without calling the District; provided the axle width does not exceed 12' wide and the overall length does not exceed 150'.

Loads exceeding the above dimensions will be individually evaluated by District personnel based on specific characteristics of load and hauling equipment.